



Talon Meter Socket Local Stock List


7500 Intervale Avenue Detroit, MI 48238



Contact John Reilly for Pricing and Product Questions: JR@ycesales.com or (313) 491-6500


DTE Energy Approved Single and Two Position Sockets

Single Position / 125 AMP / 4 Terminal / Ringless / 240VAC

DTE Number	Talon Number	Milbank Number	Terminals	Service	Hub	Connectors CU/AL		
						Line	Load	
ZSW-100	UAT111-XG	U7487-O-TG	4	UG	Blank	#6 - 2/0	#6 - 2/0	UAT111-XG


** For Air Conditioning and Electric Water Heater Interruptible Service Only*

Single Position / 200 AMP / 4 Terminal / Ringless / 240VAC

DTE Number	Talon Number	Milbank Number	Terminals	Service	Hub	Connectors CU/AL		
						Line	Load	
ZS-200	UAT317-0G	U7021-RL-TG	4	OH	Open	#6 - 350	#6 - 350	UAT417-XG
ZS-200	UAT417-0G	U7040-RL-TG	4	OH/UG	Open	#6 - 351	#6 - 351	
ZSU-200	UAT417-0G/XG	U7040-RL-TG	4	OH/UG	Open/C.P.	#6 - 352	#6 - 352	

**Field Installed Fifth Terminal Available *Units Are Supplied With Extruded Aluminum Connectors and Triplex Neutral*

Single Position / 200 AMP LEVER BYPASS / 4 & 7 Terminals / Ringless / 480VAC

DTE Number	Talon Number	Milbank Number	Terminals	Service	Hub	Connectors CU/AL		
						Line	Load	
N/A	40404-02QG	U9801-RXL	4	OH/UG	C.P.	#6 - 350	#6 - 350	40407-025
ZS3-200H	40407-025	U9701-RXL	7	OH/UG	C.P.	#6 - 351	#6 - 351	
ZS3-200P	40407-025	U9701-RXL	7	OH/UG	C.P.	#6 - 352	#6 - 352	

**BYPASS - Lever Supplies Clamping Action on Meter Spades and Also Operates as a Bypass Device*


**CONNECTORS - Units are Supplied with Extruded Aluminum Connectors and Triplex Neutral*

**Units Are Supplied with Installed Closing Plate - See Accessories for Proper Hub Size*

**Field Installed Fifth Terminal Available *Field Installed Isolated Neutral Kit Available on 40407-025*

**Field Installed Isolated Neutral Kit Available on 40407-025*


Single Position / 320 AMP LEVER BYPASS / 4 Terminal / Ringless / 240VAC

DTE Number	Talon Number	Milbank Number	Terminals	Service	Hub	Connectors CU/AL		
						Line	Load	
ZSU-320	48504-846	U1129-DTE	4	UG	Blank	3/8" - 16 Studs	3/8" - 16 Studs	48504-846

**BYPASS - Lever Supplies Clamping Action on Meter Spades and Also Operates as a Bypass Device*

**Field Installed Fifth Terminal Available*


Two Position / 200 AMP / 4 Terminal / Ringless / 240VAC

DTE Number	Talon Number	Milbank Number	Terminals	Service	Hub	Connectors CU/AL		
						Line	Load	
ZS-2	UA2716-XG	U1252-X	4	OH/UG	C.P.	3/8" - 16 Studs	#6 - 350	UA2716-XG

**Units Supplied with Installed Closing Plate *CONNECTORS—Extruded Aluminum Connectors are Tinned Plated*

**Amperage Rating - 200Amp per Position; 400 Amp Overall*

Single Position / 20 AMP CT Rated / 8 & 13 Terminals / Ringless / 480VAC

DTE Number	Talon Number	Milbank Number	Terminals	Service	Hub	Connectors CU	Meter Form	
ZS3-20-5S	9837-0908	UC6472-O-201	8	UG	Blank	#14 - #4 Max.	5S	
ZS3-20-9S	9837-0907	UC6473-O-521	13	UG	Blank	#14 - #4 Max.	6,8,9 & (alt.) 10S	

**CONNECTORS - Units are Supplied with Sleeve-Type Connectors #4 Maximum*

Accessories in stock: Hubs, Jumpers & Closing Plates

Min Order \$100

Freight Allowed \$2,000



Talon Meter Socket Local Stock List

7500 Intervale Avenue Detroit, MI 48238



Contact John Reilly for Pricing and Product Questions: JR@ycesales.com or (313) 491-6500

DTE Energy Approved TALON Uni-Pak Meter Sockets

Multi-Position / 125 AMP / 1 Phase, 3 Wire / 4 Terminal / Ring Style / 120V-240VAC

Talon Number	Enclosure Rating	Max. Socket Rating	Terminals	Bus Rating	Positions	Connectors CU/AL	
						Line	Load
WTG4411	Type N3R Outdoor	125A	4	400A	4	750MCM - 1/0	2/0 - #4
WTG4611	Type N3R Outdoor	125A	4	400A	6	750MCM - 1/0	2/0 - #4
WTG6611	Type N3R Outdoor	125A	4	600A	6	(2) 600MCM- #2	2/0 - #4



WTG6421

**Fault Rating is determined by circuit breaker rating. Circuit Breakers are sold separately*

**Field Installed Fifth Terminal Available (120/208V, 3 PHASE IN, 1 PHASE OUT, 3 Phase/4 Wire) ECMF5 (un-insulated) or ECMF5i (insulated)*

**Units Are Supplied with Extruded Aluminum Connectors*

Multi-Position / 200 AMP / 1 Phase, 3 Wire / 4 Terminal / Ring Style / 120V-240VAC

Talon Number	Enclosure Rating	Max. Socket Rating	Terminals	Bus Rating	Positions	Connectors CU/AL	
						Line	Load
WTG6412	Type N3R Outdoor	200A	4	600A	4	(2)600MCM - #2	300MCM - #4
WTG8612	Type N3R Outdoor	200A	4	800A	6	(2) 750MCM - 1/0	300MCM - #5



WTG6142

**Fault Rating is determined by circuit breaker rating. Circuit Breakers are sold separately*

**Field Installed Fifth Terminal Available (120/208V, 3 PHASE IN, 1 PHASE OUT, 3 Phase/4 Wire) ECMF5 (un-insulated) or ECMF5i (insulated)*

**Units are Supplied with Extruded Aluminum Connectors*

Consumers Energy Approved Meter Sockets

Multi-Position Horizontal Gang Sockets / 200AMP per Position / Single Phase / 3 Wire / 4 Terminals / Ringless / Horn By-Pass / 120/240VAC

Meter Position	Talon Number	Milbank Number	Terminals	Service	Hub	Connectors CU/AL	
						Line	Load
3 Position	UA3717-YPZA**	U1253-X-QG-KK-K3	4	OH/UG	C.P.	#4-600 or (2) 1/0-250	#6 - 350
4 Position	UA4719-YPZA**	U1254-X-QG-KK-K3	4	OH/UG	C.P.	#4-600 or (2) 1/0-251	#6 - 351
5 Position	UA5719-KPGP**	U1255-X-QG-KK-K3	4	OH/UG	C.P.	#2 - 600	#6 - 352
6 Position	UA6719-KPQG**	U1256-X-QG-KK-K3	4	OH/UG	C.P.	#6 - 350	#6 - 353



UA3717-YPZA

**CONNECTORS - Extruded Aluminum Connectors are Tinned Plated*

**Units Supplied with Installed Closing Plates*

***Consumers Energy will Furnish 1 and 2 Position Sockets*

Low Voltage Temporary Power Outlet Panel

TL137US	Power Outlet Panel. Receptacles included: 14-50R rated 125/250V (50A), TT30R rated 125V (30A), 5-20R2GFI rated 125V (20A). Unmetered
TL77US	Power Outlet Panel. Receptacles included: 5-20R2GFI rated 125V (20A), 5-20R2GFI rated 125V (20A), Unmetered:



TL37US

Min Order \$100
Freight Allowed \$2,000